

Page 2A-2, Section, 2A.03, Between Lines 5 and 6

Various Transportation Agencies within the State may have their own preferences or standards that comply with the stipulations within this manual. Sign designers are encouraged to verify if the transportation agency, responsible for the roadway of consideration, has such preferences or standards.

Page 2A-2 Section 2A.03 Line 9

Results from traffic engineering studies, or engineering judgment, of physical and traffic factors should indicate

Page 2A-11, Section 2A.15, Line 24

(2 in) wide, ~~or on larger signs, 75 mm (3 in) wide~~. Where practicable, the corners of the

Page 2A-11 Section 2A.15 Between Lines 25 and 26

Option:

On larger signs, as determined by engineering judgment, the border may be 75 mm (3 in) wide.

Page 2A-21 Section 2A.18 Between Lines 16 and 17

The following mounting height standards shall be applicable for general conditions. General minimum and maximum mounting height shall apply to sign installations unless otherwise required by other Standards or permitted by other Guidance or Options within this manual.

Page 2A-21 Section 2A.18 Lines 18 and 19

(5 ft), measured from the bottom of the sign to the level of the near edge of the pavement. Where parking or pedestrian movements occur on an expected recurring basis, the clearance to the bottom of the

Page 2A-21, Section 2A.18, Lines 22 to 24

minimum height of 2.1 m (7 ft). If a secondary sign is mounted below another sign, the ~~major~~ secondary sign shall be installed ~~at least 2.4 m (8 ft) and the secondary sign~~ at least 1.5 m (5 ft) above the level of the pavement edge. All route signs, warning signs,

Page 2A-21, Section 2A.18, Line 30

structures. The vertical clearance to overhead sign structures or supports ~~shall~~ need not

Page 2A-22, Section 2A.18, Line 17

Figure 2A – 1 illustrates some of the mounting heights ~~requirements contained~~ described in this section.

Page 2A-22 Section 2A.19 Between Lines 19 and 20

The following lateral offset standard shall be applicable for general conditions. General minimum and maximum lateral offset shall apply to sign installations unless otherwise required by other Standards or permitted by other Guidance or Options within this manual.